

## The Big Hit on European Roofs.

Vapour permeable roofing underlay – protects even in extreme conditions.

Σ

Σ

œ




For perfect, dry, thermal insulation – rely on the DELTA®System!


#### **Trust the Number 1:**

## **DELTA®-MAXX**

## **Exceptionally tough. Completely**









Very tear resistant and extremely sure footing.


DELTA®- MAXX is absolutely waterproof.

# AXX

## y impervious.

#### DELTA®-MAXX ...

- ... is Germany's most popular vapour permeable underlay for fully insulate pitched roofs.
- ... is highly reliable, with 15 years of experience.
- ... is fire resistant Class E EN 13501-1, B 1 rating (DIN 4102).
- ... allows vapour to permeate with great ease (with an S<sub>d</sub> value of approx.
   0.15 m) ensuring that ambient room moisture can escape.
- ... can be laid quickly and efficiently thanks to its smooth, fabric bottom side.
- ... makes laying easy, with its squareridged surface profile: helps you cut straight edges.
- ... makes condensation calculations a thing of the past.
- ... is together with DELTA®-MAXX TITAN Thermomembrane and DELTA®-MAXX PLUS energy-saving membrane the only underlay available with a moisture retaining surface.
- ... can, in extreme situations, absorb up to 1 litre/m² through its bottom surface, gradually releasing this later up into the outside air.
- ... ensures extremely sure footing when working with ladders on roof battens.
- ... is very tear resistant (approx. 450/300 N/5 cm).
- ... can be unrolled and lined up very quickly.



DELTA®-MAXX – Germany's most popular underlay for pitched roof

#### Why not profit from the DELTA® System?

#### Outside ...

DELTA'Sy

... DELTA®-MAXX vapour permeable, tear-resistant roofing underlay for fully insulated pitched roofs. With moisture retaining surface. Perfect thermal insulation from A to Z.

#### Inside ...

... a DELTA®-REFLEX air and vapour barrier; as DELTA®-REFLEX PLUS with integrated self-adhesive border. An energy-saving sheet made of rugged, highly flexible 4-ply material. Reflects heat and saves on heating costs. Provides protection from electrical smog.

Needless to say, we have a range of perfect accessories, of which you find additional information on the next page.



#### **DELTA®-MAXX**

#### Technical Data Overview:

Teelinean Data of the trees.	
Material	Highly tear-resistant polyester felt with vapour permeable polyurethane coating.
Application	On fully insulated pitched roofs without sheathing, and as protection for building facades.
Fire resistance	Class E (EN 13501-1) B 1 rating (DIN 4102)
Tensile strength	approx. 450/300 N/5 cm (EN 12311-1+2)
Watertightness	Watertight W 1 (EN 13859-1+2)
S <sub>d</sub> value	approx. 0.15 m
Service temperature range	- 40 °C to + 80 °C
Weight	approx. 190 g/m²
Roll weight	approx. 14 kg
Roll size	50 m x 1.5 m

Due to variable weather and UV conditions we recommend the efficient covering of our sheets.

### **DELTA®-Accessories** for DELTA®-MAXX.

#### Dörken makes your life easier - systematically.

You are sure to appreciate these handy DELTA®-Accessories:



#### DELTA®-MULTI-BAND

All-round adhesive tape featuring top adhesion. For all DELTA® sheets for interior and exterior application, particularly for sealing overlaps and openings and repairing tears.



#### **DELTA®-THAN**

Permanently elastic sealing compound for fixing and seam jointing of DELTA® sheet products. Also can be used to secure connections



#### DELTA®-SCHAUM-BAND SB 60

Single-faced adhesive tape for sealing nail penetrations between counterbattens and waterproofing sheets.



#### **DELTA®-FLEXX-BAND**

Stretchable sealing tape for inner and outer connections to structural details such as skylights, dormer windows, ventilator exhaust pipes, cables etc.





Dörken GmbH & Co. KG
Wetterstraße 58
D-58313 Herdecke
Tel.: +49 23 30/63-0
Fax: +49 23 30/63-355
bvf@doerken.de
www.doerken.com

Standard requests for tender as well as detailed installation instructions for all DELTA®-Products may be obtained at www.doerken.com as pdf files for you to print out and save.